

Compression Fittings: Stainless Steel



Need adjustable fittings?
We also offer single PTFE ferrules

PTFE FERRULES

| Part # | To suit probe OD |
|--------|------------------|
| CTF-16 | 1/16" |
| CTF-18 | 1/8" |
| CTF-36 | 3/16" |
| CTF-14 | 1/4" |
| CTF-56 | 5/16" |
| CTF-38 | 3/8" |
| CTF-12 | 1/2" |

SS316 w/ DOUBLE FERRULES

| Part # | Thread Size | To suit probe OD |
|--------|-------------|------------------|
| C18-18 | 1/8" NPT | 1/8" |
| C18-36 | 1/8" NPT | 3/16" |
| C18-14 | 1/8" NPT | 1/4" |
| C14-18 | 1/4" NPT | 1/8" |
| C14-36 | 1/4" NPT | 3/16" |
| C14-14 | 1/4" NPT | 1/4" |
| C12-18 | 1/2" NPT | 1/8" |
| C12-36 | 1/2" NPT | 3/16" |
| C12-14 | 1/2" NPT | 1/4" |

SS316 w/ SINGLE FERRULE

| Part # | Thread Size | To suit probe OD |
|-------------|-------------|------------------|
| SC16-16-BT1 | 1/16" NPT | 1/16" |
| SC18-16-BT1 | 1/8" NPT | 1/16" |
| SC18-18-BT1 | 1/8" NPT | 1/8" |
| SC18-36-BT1 | 1/8" NPT | 3/16" |
| SC18-14-BT1 | 1/8" NPT | 1/4" |
| SC14-16-BT1 | 1/4" NPT | 1/16" |
| SC14-18-BT1 | 1/4" NPT | 1/8" |
| SC14-36-BT1 | 1/4" NPT | 3/16" |
| SC14-14-BT1 | 1/4" NPT | 1/4" |
| SC14-56-BT1 | 1/4" NPT | 5/16" |
| SC14-38-BT1 | 1/4" NPT | 3/8" |
| SC38-18-BT1 | 3/8" NPT | 1/8" |
| SC38-36-BT1 | 3/8" NPT | 3/16" |
| SC38-14-BT1 | 3/8" NPT | 1/4" |
| SC38-38-BT1 | 3/8" NPT | 3/8" |
| SC12-18-BT1 | 1/2" NPT | 1/8" |
| SC12-36-BT1 | 1/2" NPT | 3/16" |
| SC12-14-BT1 | 1/2" NPT | 1/4" |
| SC12-56-BT1 | 1/2" NPT | 5/16" |
| SC12-38-BT1 | 1/2" NPT | 3/8" |
| SC12-12-BT1 | 1/2" NPT | 1/2" |

- Bore through fittings
- All NPT threads cut on CNC turning centers - rolled threads are optional at a small price adder
- Bores of compression fitting bodies are drilled and then reamed to give a smooth internal finish and accurate dimensions
- Ferrule seats are burnished to ensure accurate seating
- Spare SS316 Ferrules & Nuts available
- Other sizes, incl. metric are available upon request
- Single ferrule fittings - compare to Parker
- Double ferrule fittings - compare to Swagelok